



CB-52 5MP Bullet with Zoom

CB-52 (5 MP Bullet with Zoom 2.8 ~ 12mm)	
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS
Lens	2.8 ~ 12mm
Angle Of View (H)	96.4°~32.7°
Angle Of View (V)	51.3°~18.6°
Angle Of View (O)	101.2°~37.2°
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 50m (164ft)
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	15 FPS (recommended) to 25 FPS (2880 x 1620)
Audio	
Supported	Yes
Certifications	
Certifications	UL: UL 62368-1 FCC: FCC 47 CFR part15 B

General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 9.6W
Dimensions (L × W × H)	206 × 73 × 73mm (8.1" × 2.9" × 2.9")
Net Weight	0.51kg(1.12lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
ONVIF and NDAA	Yes